

## Water Bath

### NSW-128-A

### WATER BATH RECTANGULAR DOUBLE WALL

#### CONSTRUCTION:

- Double walled, inside made of Stainless Steel 304 Qlty.
- Outside Mild Steel sheet painted in Epoxy Powder Coating.
- 25mm insulation with the mineral wool.
- With concentric rings which are made of stainless steel 304 qty.
- Microprocessor based controller Digital LED display of temperature with set value & Process value cum Indicator.  $100^{\circ}\text{C} \pm 1^{\circ}\text{C}$
- With wire and plug but without thermometer.
- It has option to control precise temperature  $\pm 0.5^{\circ}\text{C}$  by Option-1 is compulsory to be attached.**



NSW-128 SMART

#### SIZE INSIDE CHAMBER (STAINLESS STEEL 304 Qlty.)

MODEL	SIZE (MM)			HOLES DIA	LTRS	RATING
	L	W	H			
BRD-1	300	250	100	6 Holes of 75mm dia	8	1.0 KW
BRD-2	355	405	100	12 Holes of 75mm dia	15	1.5 KW
BRD-3	655	655	100	18 Holes of 75mm dia	44	4.0 KW
BRD-4	710	810	100	24 Holes of 75mm dia	58	4.0 KW

#### OPTIONAL:

- Stirrer with 1/20 H.P. High Speed motor with stainless steel stirring rod with blade having speed controller to cost extra.
- Microprocessed PID Controller having 4 ramp & 4 soak profile having set mode, alarm parameter, configuration parameter, profile parameter, set point profile, PV error indicator, parameter for locking etc to cost extra.
- Alarm: It is possible to provide electronic alarm if, temperature deviates more than  $\pm 1^{\circ}\text{C}$ . to cost extra.
- Option-1 is compulsory to be attached with Option-2



NSW-128