

Water Bath

NSW-127

WATER BATH RECTANGULAR (SINGLE WALL ELECTRIC)

CONSTRUCTION:

- Made of Stainless Steel Sheet 304 qlty
- Concentric rings are also made of stainless steel.
- Heating elements have an automatic cut off device when the bath gets dry.
- With arrangement of 6 holes or 12 holes.
- Electrically operated on 220/230V AC



NSW-127

SIZE INSIDE CHAMBER:

MODEL	SIZE (MM)			HOLES DIA	LTRS	RATING
	L	W	H			
BSS-1	300	250	100	6 Holes of 75mm dia	8	1.0 KW
BSS-2	355	405	100	12 Holes of 75mm dia	15	1.5 KW

NSW-128

WATER BATH RECTANGULAR DOUBLE WALL (THERMOSTATIC CONTROL)

CONSTRUCTION:

- Double walled, inside made of Stainless Steel 304 Qlty.
- Outside Mild Steel sheet painted in Epoxy Powder Coating.
- 25mm insulation with the mineral wool.
- With concentric rings which are made of stainless steel 304 qlty.
- Temperature by a thermostat from few °C above ambient to 100°C ± 1°C.
- With wire and plug but without thermometer.



NSW-128

SIZE INSIDE CHAMBER (STAINLESS STEEL 304 QLTY.)

MODEL	SIZE (MM)			HOLES DIA	LTRS	RATING
	L	W	H			
BRS-1	300	250	100	6 Holes of 75mm dia	8	1.0 KW
BRS-2	355	405	100	12 Holes of 75mm dia	15	1.5 KW
BRS-3	655	655	100	18 Holes of 75mm dia	44	4.0 KW
BRS-4	710	810	100	24 Holes of 75mm dia	58	4.0 KW

OPTIONAL:

- Stirrer with 1/20 H.P. High Speed motor with stainless steel stirring rod with blade having speed controller to cost extra.
- Microprocessor based controller with LED display Digital Temperature Controller cum Indicator instead of thermostat to cost extra.
- Microprocessed PID Controller having 4 ramp & 4 soak profile having set mode, alarm parameter, configuration parameter, profile parameter, set point profile, PV error indicator, parameter for locking etc to cost extra.
- Alarm: It is possible to provide electronic alarm if, temperature deviates more than ± 1°C. to cost extra.
- Option-1 Is compulsory to be attached with Option-2
- Option-1 Is compulsory to be attached with Option-3