

Ovens

NSW-143

OVEN UNIVERSAL (THERMOSTATIC CONTROL)

CONSTRUCTION:

- Double walled inside Aluminium/Stainless Steel 304 qty.
- Outside made of Mild steel and painted in Epoxy Powder Coating.
- Insulation of 75mm by mineral wool.
- Heating Elements are on 'three sides' bottom LHS & RHS ribs
- The door has neoprene rubber gasket.
- Adjustable air ventilators on two sides.
- Supplied with Perforated adjustable shelves.
- Supplied with / without air circulating fan.
- "L" shaped thermometer 0°C to 250°C.

TEMPERATURE :

- Controlled by a precision thermostat temperature range from few above ambient to 250°C ±1°C.
- Two indicators, one On/Off Switch and Thermostat.
- To Work on 220/230V AC



NSW-143

SIZE INSIDE CHAMBER (ALUMINIUM)

MODEL	SIZE (MM)			RATING	LTRS
	W	D	H		
OUA -1	300	300	300	1.0 KW	28
OUA -2	355	355	355	1.0 KW	45
OUA -3	455	455	455	1.5 KW	95
OUA -4	455	455	605	1.5 KW	125
OUA -5	605	605	605	2.0 KW	224
OUA -6	605	455	910	2.0 KW	252
OUA -7	605	605	910	2.0 KW	336

SIZE INSIDE CHAMBER (STAINLESS STEEL)

MODEL	SIZE (MM)			RATING	LTRS
	W	D	H		
OUS -1	300	300	300	1.0 KW	28
OUS -2	355	355	355	1.0 KW	45
OUS -3	455	455	455	1.5 KW	95
OUS -4	455	455	605	1.5 KW	125
OUS -5	605	605	605	2.0 KW	224
OUS -6	605	455	910	2.0 KW	252
OUS -7	605	605	910	2.0 KW	336

Note: Electronic digital temperature controller-cum-indicator cannot be fitted in Hot Air Oven.