

Incubator

NSW-152 B.O.D INCUBATOR SUPER DELUXE AUTOMATIC

Other specification as above but fitted with very precise Microprocessed Electronic Digital Controller Cum Indicator with an accuracy of $\pm 0.5\text{ }^{\circ}\text{C}$ with Electronic Digital voltmeter



NSW-152 B.O.D
(SUPER DELUXE MODEL)

SIZE INSIDE CHAMBER:

MODEL	SIZE (MM)			LTRS	RATING
	W	D	H		
LTS-S 2.6 Cu.Ft	415	430	425	75	3.0 KW
LTS-M 4 Cu.Ft	455	410	610	112	3.0 KW
LTS-1 6.1Cu.Ft	505	415	830	171	3.0 KW
LTS-2 10 Cu.Ft	570	415	875	280	3.0 KW
LTS-3 12 Cu.Ft	650	580	900	336	3.5 KW
LTS-4 15 Cu.Ft	700	640	900	425	3.5 KW

OPTIONAL:

- Interior lighting arrangement with Timer 0-24 hours (cannot be fitted in 2.6 & 4 cu.ft. size)
- Incubation in CO₂/ air mixture or air/CO₂ mixtures, similar nozzle is provided to cost extra
- Humidity control from 55% to 95% by Microprocessed Digital Temp. Controller & RH control with SV & PV. to cost extra
- Alarm: It is possible to provide electronic alarm if, temperature deviates more than $\pm 1^{\circ}\text{C}$. to cost extra
- LCD, version display & control with PC Interface or printer interface software 8 channel data logger temperature recording with RS-485 PC communication, data can be collect through USB Port to cost extra.
- Automatic Co₂ Injector in the chamber for sterilization with solenoid valve, UV tube and 7 days programmable timer to cost extra.
- 2KVA UPS with 30 min backup for controller to cost extra
- **Inside chamber and shelves can be made of Stainless Steel 304 qty. instead of Anodized Aluminium to cost extra**

SIZE INSIDE CHAMBER:

2.6 Cu.Ft
4 Cu.Ft
6.1 Cu.Ft
10 Cu.Ft
12 Cu.Ft
15 Cu.Ft